

- ▶ Compatible with TTK Digital & Analog Systems
- ▶ Detects Water & Base Liquids
- ▶ Pre-connected in Standard Lengths

Description

The TTK sense cable FG-ECS detects the presence of conductive liquids at any point along its length. The FG-ECS sense cable connects to TTK's analog alarms (FG-ALS & FG-A) or digital units (FG-NET & FG-SYS), to respond immediately in the event of any leaks of liquids.

Features & Benefits

A RELIABLE SENSE CABLE

The FG-ECS sense cable performs the following functions:

- Rapidly detects the leak of any liquid along the length of the cable.
- Detects leaks the nearest metre when connected to the locating units: FG-NET, FG-SYS or FG-ALS.
- Detects any break or cut to the cable.
- Non-absorbant design can be reset in seconds after removal of the leak.

A MODULAR SYSTEM

The FG-ECS cable ensures permanent protection in areas at risk. FG-ECS is available in standard and pre-finished lengths of 3, 7 or 15 metres.

The sense cable is installed to provide the best possible protection in order to cover risks and limit the financial consequences of an undetected leak.

EASY INSTALLATION

A spliced junction with a length of 3.5 metres of Belden jumper cable and an end termination at each length of FG-ECS sense cable give quick connection to the unit or to the sector diversion box

Fixing clips are used to fasten the sensing cables in the chosen areas. A set of neutral jumper cables and pre-finished connection accessories gives continuity to each circuit with the sector diversion box FG-DTCS.

A TOUGH AND STURDY DESIGN

Small in diameter, the FG-ECS sense cable is light, flexible and of an easily identifiable colour. Its helical jacket construction, compression connected on an extruded central core, reduces the risk of contamination and false alarms. It is made from the highest quality materials which are abrasive resistant in hostile environments.

Technical Data

Compatibility	Digital units: FG-SYS, FG-NET, FG-BBOX (via Diversion Box: FG-DTCS) Analog units: FG-ALS, FG-A
Maximum Rated Temperature	85°C
Weight	25g per metre
Sense Cable Diameter	7.5 mm with PEHD jacket
Core Material	Flame-retardant low-smoke HDPE-based polymer
Liquid Quantity to Active Alarm	50-100mm on the sense cable
Drying Time	10 seconds after drying the sense cable
FG-ECS Colour	Dark blue

Product Diagram




FG-ECS Sense Cable Belden Tip



FG-ECS Sense Cable End Termination Tip

2 Communication Wires and
2 Wires for Locating



2 Black and White Sense Wires

2 Continuity Wires

Identification Codes

FG-ECS15	Sector water and base sense cable in 15m length
FG-ECS7	Sector water and base sense cable in 7m length
FG-ECS3	Sector water and base sense cable in 3m length
FG-ECS Random (400m)	Sector water and base sense cable in roll of 400m
Accessories:	
FG-DTCS	Addressable box
CFE-100C	100 hold-down clips with cold adhesive glue
ES40	40 signal tags

Certificate



This brochure has been carefully prepared to ensure technical accuracy but is only intended for promotional use. TTK cannot guarantee that the information contained herein contains no errors or omissions, and hence does not accept responsibility related to the use of its equipment. TTK maintain its obligations set forth in the Standard Terms and Conditions of Sale and will not, under any circumstances, assume liability for any incidental damages, indirect or consequential, arising from the sale, resale, use or misuse of this project. The purchaser(s) accept their responsibility as the sole judge(s) of the adaptability of the product for the intended use.

- **TTK Headquarters** / 4 rue du Chemin Vert, 92110 Clichy, France / T : +33.1.56.76.90.10 / F : +33.1.55.90.62.15 / www.ttk.fr / ventes@ttk.fr
- **TTK UK Ltd.** / 3 Luke Street London EC2A 4PX - United Kingdom / T : +44 207 729 6002 / F : +44 207 729 6003 / www.ttkuk.com / sales@ttkuk.com
- **TTK Pte Ltd.** / #09-05, Shenton House, 3 Shenton Way / Singapore 068805 / T : +65.6220.2068 / M : +65.9271.6191 / F : +65-6220.2026 / www.ttk.sg / info@ttk.sg
- **TTK Asia Ltd.** / 2107-2108 Kai Tak Commercial Building / 317 Des Voeux Road Central / Hongkong / T : +852.2858.7128 / F : +852.2858.8428 / www.ttkasia.com / info@ttkasia.com
- **TTK Middle East FZCO** / Building 6EA, Office 510 PO Box 54925 / Dubai Airport Free Zone / UAE / T : +971 4 70 17 553 / M : +971 50 259 66 29 / www.ttkuk.com / cgalmiche@ttk.fr
- **TTK Deutschland GmbH** / Berner Strasse 34, 60437 Frankfurt, Deutschland / T : +49(0)69-95005630 / F : +49(0)69-95005640 / www.ttk.fr/de/ / vertrieb@ttk-gmbh.de